

学校编号: 10384
学 号: 20520050153252

分类号 _____ 密级 _____
UDC _____

厦 门 大 学

博 士 学 位 论 文

碳纳米管负载/促进合成气制低碳混合醇
Ni-Mo-K 氧化物基催化剂的研究

Study of MWCNTs Supported/Promoted Ni-Mo-K
Oxide-Based Catalysts for Higher Alcohol Synthesis
from Syngas

马 春 辉

指导教师姓名: 张 鸿 斌 教 授

专 业 名 称: 物 理 化 学

论文提交日期: 2 0 1 0 年 5 月

论文答辩日期: 2 0 1 0 年 6 月

学位授予日期: 2 0 1 0 年 月

答辩委员会主席: _____

评 阅 人: _____

2010 年 5 月

厦门大学学位论文原创性声明

本人呈交的学位论文是本人在导师指导下,独立完成的研究成果。本人在论文写作中参考其他个人或集体已经发表的研究成果,均在文中以适当方式明确标明,并符合法律规范和《厦门大学研究生学术活动规范(试行)》。

另外,该学位论文为()课题(组)的研究成果,获得()课题(组)经费或实验室的资助,在()实验室完成。(请在以上括号内填写课题或课题组负责人或实验室名称,未有此项声明内容的,可以不作特别声明。)

声明人(签名):

年 月 日

厦门大学学位论文著作权使用声明

本人同意厦门大学根据《中华人民共和国学位条例暂行实施办法》等规定保留和使用此学位论文，并向主管部门或其指定机构送交学位论文（包括纸质版和电子版），允许学位论文进入厦门大学图书馆及其数据库被查阅、借阅。本人同意厦门大学将学位论文加入全国博士、硕士学位论文共建单位数据库进行检索，将学位论文的标题和摘要汇编出版，采用影印、缩印或者其它方式合理复制学位论文。

本学位论文属于：

（ ） 1. 经厦门大学保密委员会审查核定的保密学位论文，
于 年 月 日解密，解密后适用上述授权。

（ ） 2. 不保密，适用上述授权。

（请在以上相应括号内打“√”或填上相应内容。保密学位论文应是已经厦门大学保密委员会审定过的学位论文，未经厦门大学保密委员会审定的学位论文均为公开学位论文。此声明栏不填写的，默认为公开学位论文，均适用上述授权。）

声明人（签名）：

年 月 日

扩展式中文摘要

煤基低碳醇醚燃料（包括甲醇、低碳混合醇和二甲醚）是基于能源化工原料多样化具有战略意义的燃料化学品。甲醇和低碳醇均已被证实是高辛烷值、低污染的车用合成燃料或燃料添加剂。自上个世纪 70 年代末世界经济受二次石油危机冲击后，由煤（或天然气）基合成气制取低碳混合醇的研究一度受到重视并取得一定进展；但迄今的低碳醇合成工艺，其原料合成气单程转化率及生成 C_{2+} -醇的选择性均较低，大多数体系的主要产物仍是甲醇或低碳烃，而非低碳（ C_{2+} ）醇，至今国际上尚无大型化低碳醇合成生产装置。近年来由于环保方面的原因，甲基叔丁基醚（MTBE）作为油品添加剂在一些国家和地区已被禁用，使得低碳醇作为油品添加剂的实用价值倍增，低碳醇合成工艺的工业化重新引起燃料化工界的兴趣。如何提高催化剂的活性和选择性以提高生产效率，成为制约低碳醇合成工艺实用化和工业化的技术瓶颈。

多壁碳纳米管（简称为 CNTs）自 1991 年发现以来，人们对它的兴趣与日俱增。这类新型纳米碳材料在结构上与中空的石墨纤维相近，但其结构规整性较高，具有石墨化的管壁、纳米级的管腔、由 sp^2 -C 构成的表面，并展现出良好的导电导热性、以及对 H_2 的吸附活化并促进吸附氢溢流的优良性能，所有这些使 CNTs 很有希望成为新型的催化剂载体或促进剂。迄今报道有关 CNTs 的催化应用领域涵盖选择加氢、氢甲酰化、氨合成、F-T 合成、甲醇/低碳醇合成、脱氢、选择氧化和电催化等。从化学催化角度考虑，碳纳米管对 H_2 强的吸附活化能力以及对氢溢流的促进作用很值得注意；利用某些过渡金属对 CNTs 进行适当修饰可望进一步提高其助催化性能。

本文开展 CO 加氢制低碳醇用的 CNTs 促进的高效新型 Ni-Mo-K 氧化物基催化剂的开发研究，从负载型 Ni-Mo-K 催化剂的应用基础研究入手，在初步弄清 CNTs 促进作用的基础上，进而研发出一类金属 Ni 修饰 CNTs 促进的高效新型 Ni-Mo-K 氧化物基催化剂，取得如下兼具理论和实用价值的重要进展。

1. CO 加氢制低碳醇用 CNTs 负载 Ni-Mo-K 氧化物基催化剂的开发研究

1.1 CNTs 负载 Ni-Mo-K 氧化物基催化剂的制备及催化性能

用自行制备的一种鱼骨型多壁碳纳米管（记为 CNTs）作为载体，由分步等容浸渍法制备 CNTs-负载的 Ni-Mo-K 氧化物基催化剂（记为 $x\%\text{Ni}_i\text{Mo}_j\text{K}_k/\text{CNTs}$ ， $x\%$ 为质量分数），在加压固定床连续流动反应系统上，评价其对 CO 加氢制低碳醇的催化性能，并与常规载体活性炭（AC）负载的参比物、以及不含 CNTs 的非负载共沉淀基质体系作比较。结果表明，在组成优化的 $15\%\text{Ni}_1\text{Mo}_1\text{K}_{0.05}/\text{CNTs}$ 催化剂上，在 5.0 MPa，538 K， $\text{H}_2/\text{CO}/\text{N}_2 = 45/45/10$ (v/v)， $\text{GHSV}(\text{outlet}) = 5000 \text{ mL}_{\text{STP}} \cdot \text{h}^{-1} \cdot \text{g}_{\text{cat}}^{-1}(\text{outlet})$ 的反应条件下，CO 加氢的转化率达 11.9%，相应总含氧加氢化物（ C_{1-3} -醇+DME）的时空产率达 $205 \text{ mg} \cdot \text{h}^{-1} \cdot \text{g}_{\text{cat}}^{-1}$ 。这个值是相同条件下 AC 负载最佳($\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$)-载量的参比催化剂（ $35\%\text{Ni}_1\text{Mo}_1\text{K}_{0.05}/\text{AC}$ ）的相应值（ $176 \text{ mg} \cdot \text{h}^{-1} \cdot \text{g}_{\text{cat}}^{-1}$ ）的 1.16 倍，是不含 CNTs 的非负载共沉淀基质体系（ $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$ ）的相应值（ $116 \text{ mg} \cdot \text{h}^{-1} \cdot \text{g}_{\text{cat}}^{-1}$ ）的 1.76 倍。

1.2 CNTs 负载 Ni-Mo-K 氧化物基催化剂的表征

催化剂的物化（XRD，XPS， H_2 -TPD 和 LRS 等）表征结果揭示，CNTs-载体通过其与被担载 Ni-Mo 组分的相互作用，对催化剂的化学态产生强烈影响，导致工作态催化剂上与低碳醇的生成密切相关的两类表面催化活性物种， $\text{NiO}(\text{OH})$ 和 $\text{Mo}^{4+}/\text{Mo}^{5+}$ ，的摩尔分率明显增加，相应地，与烃的生成（尤其 CO 加氢甲烷化）密切相关的两类表面催化活性物种， Ni^0 和 Mo^0 ，的摩尔分率大为下降。此外，CNTs 载体还为 H_2 的吸附活化提供 sp^2 -C 表面活性位。所有这些因素都有助于 CO 加氢生成 C_{1-3} -醇的选择性的提高。

2. CO 加氢制低碳醇用 Ni 修饰 CNTs 促进的共沉淀型 Ni-Mo-K 氧化物基催化剂的开发研究

2.1 金属镍修饰 CNTs-基纳米材料的研制

以自行制备的一种鱼骨型 CNTs 作为基质，用微波助多元醇液相还原沉积法制备一类金属 Ni-修饰的 CNTs，记为 $y\%\text{Ni}/\text{CNTs}$ （ $y\%$ 为质量百分数）。所制得的复合材料的 TEM/SEM 观测结果显示，金属 Ni 相当均匀地高度分散在 CNTs 表面；利用 Scherrer 公式，从金属 Ni 的 XRD 特征衍射峰的半峰宽度可估算出其粒径在 6 nm 以下。组成为

4.8%Ni/CNTs 试样的 EDX 分析显示, C、O、Ni 为该试样表面层仅有的 3 种元素, 其原子百分率分别为 94.4%、4.5%和 1.1%。H₂-TPD 测试揭示, 适量金属 Ni 对 CNTs 表面的修饰导致其对 H₂ 的吸附容量显著增加, 以组成 4.8%Ni/CNTs 试样对 H₂ 的吸附容量增幅最大 (两试样在 293~873 K 温度范围的 H₂-TPD 曲线的相对面积强度比为 $S_{4.8\%Ni/CNTs}/S_{CNTs} = 100/32$, 增幅达 212%)。

2.2 金属 Ni 修饰 CNTs 促进的共沉淀型 Ni-Mo-K 氧化物基催化剂的制备和催化性能

用上述制备的金属 Ni 修饰的 CNTs (y%Ni/CNTs) 作为促进剂, 制备 y%Ni/CNTs-促进的共沉淀型 Ni-Mo-K 催化剂, 记为 Ni_iMo_jK_k-x%(y%Ni/CNTs) (x%和 y%均为质量百分数)。在加压固定床连续流动反应系统上评价其对 CO 加氢制低碳醇的催化性能, 并与添加等量纯 CNTs 的对应物和不添加 CNTs 的原基质催化剂作比较。结果表明, 在组成经优化的 Ni₁Mo₁K_{0.05}-10.8%(4.8%Ni/CNTs)催化剂上, 在 5.0 MPa、558 K、H₂/CO/N₂ = 45/45/10 (v/v) 和 5000 mL_{STP}·h⁻¹·g_{-cat}⁻¹ (outlet) 的反应条件下, CO 加氢的转化率达 18.0%, 总加氢含氧产物 (C₁₋₃-醇+DME) 的时空产率达 379 mg·h⁻¹·g_{-cat}⁻¹; 这个值是添加等量纯 CNTs 的对应物 Ni₁Mo₁K_{0.05}-10.8%CNTs 的相应值 (317 mg·h⁻¹·g_{-cat}⁻¹) 的 1.2 倍, 是不添加 CNTs 的原基质催化剂 Ni₁Mo₁K_{0.05} 的相应值 (218 mg·h⁻¹·g_{-cat}⁻¹) 的 1.7 倍。在总加氢产物中, (C₁₋₃-醇+DME) 的 C-基选择性达 70.3%, 以 EtOH 为主要加氢产物, 其 C-基选择性达 24.2%, 展现其作为优质车用动力燃料添加剂和化工原料的重要应用前景。

2.3 金属 Ni 修饰 CNTs 促进的共沉淀型 Ni-Mo-K 氧化物基催化剂的表征

表观活化能的测试结果表明, 添加少量 CNTs-基促进剂于共沉淀型 Ni-Mo-K 氧化物基催化剂中并不引起 CO 加氢反应的表观活化能发生明显变化, 暗示少量碳纳米管基促进剂的参与并不导致 CO 加氢制低碳醇反应的速率决定步骤有所改变。催化剂的氧化态前驱物的 H₂-TPR 测试结果显示, 与不添加 CNTs 基促进剂的共沉淀基质体系相比, 添加 CNTs 基促进剂的体系更易于在较低温度下还原活化。工作态催化剂的 XRD 和 XPS 谱揭示, CNTs-基促进剂通过其与 Ni-Mo 组分的相互作用, 对催化剂的化学态有显著影响, 导致在工作态催化剂表面, 与低碳醇生成密切相关的两类催化活性物种, NiO(OH)

和 $\text{Mo}^{4+}/\text{Mo}^{5+}$ ，的摩尔分率明显增加，与此同时，与烃的生成（尤其是 CO 加氢甲烷化）密切相关的两类催化活性物种， Ni^0 和 Mo^0 ，的摩尔分率大为下降。 H_2 -TPD 和 LRS 联合表征结果揭示，CNTs-基促进剂对 H_2 强的吸附能力在工作态催化剂表面营造高浓度的 sp^2 -C-H 吸附物种的微环境，于是有助于提高一系列表面加氢反应的速率，并抑制水煤气变换副反应。所有这些因素对 $\text{C}_{1\sim3}$ -醇产率的提高都有不同程度的贡献。

对比研究揭示，与由类石墨平面“边沿原子”构建而成的鱼骨型多壁碳纳米管管壁表面富含悬键的情形不同，平行型多壁碳纳米管的管壁表面系由类石墨平面“面内原子”构建而成，较少悬键，化学活性较低，相应工作态催化剂表面 sp^2 -C-H 形态的 H-吸附物种的浓度较低，其促进作用不如鱼骨型 CNTs 显著。在相同条件下，添加等量平行型 CNTs 的催化剂上低碳醇醚产物（ $\text{C}_{1\sim3}$ -醇+DME）的单程时空产率只及添加以鱼骨型 CNTs 的对应体系的 67%（即：212 : 317 ($\text{mg}\cdot\text{h}^{-1}\cdot\text{g}_{\text{cat}}^{-1}$)，在 5.0 MPa、558 K 的反应条件下）。同为碳素材料的 AC（一种比表面积高达 830 m^2/g 的无定形碳），由于其不具备 CNTs 特有的纳米级石墨化管壁结构，等量 AC 的掺入不仅无助于 $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$ 基质催化剂性能的提高，反而导致 CO 加氢转化率和低碳醇醚产率有所下降（可能由于其对 Ni-Mo 活性组分的稀释之故）。

3. 结论

- 1) CNTs-基纳米材料（包括纯 CNTs 和金属 Ni-修饰 CNTs）能作为合成气加氢转化制低碳醇用 Ni-Mo-K 氧化物基催化剂的优良载体或促进剂。在本文研制的 CNTs-基纳米材料负载或促进的 $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$ 氧化物基催化剂上，在经优化的反应条件下，合成气加氢转化均显示出高的生成 $\text{C}_{1\sim3}$ -醇的选择性。
- 2) CNTs-基纳米材料的促进作用主要表现在：a) 为反应物之一的 H_2 的吸附活化提供 sp^2 -C 表面活性位，在工作态催化剂表面营造高浓度 sp^2 -C-H 吸附物种的微环境；b) 通过影响催化剂的化学态，促进工作态催化剂表面与低碳醇醚生成密切相关的两种催化活性物种， $\text{NiO}(\text{OH})$ 和 $\text{Mo}^{4+}/\text{Mo}^{5+}$ ，的摩尔分率显著提高。
- 3) 少量金属 Ni 对 CNTs 的适当修饰能提高 CNTs 对 H_2 的吸附能力，使其促进作用更显著。

4. 本文的创新点

- 研发出一种金属 Ni 修饰 CNTs 促进的高效新型 Ni-Mo-K 氧化物基催化剂，所制备的催化剂用于合成气加氢转化，能有效地提高生成低碳醇醚（C_{1~3}-醇+DME）的选择性和单程产率，具有实用前景。
- 初步弄清作为载体或添加剂的 CNTs-基纳米材料的促进作用本质，对于深化对 CNTs-基纳米材料的催化特性的认识具有理论意义。

关键词：多壁碳纳米管；金属 Ni-修饰碳纳米管；Ni-Mo-K 催化剂；CO 加氢；低碳醇合成

Extended Abstract

The higher alcohols (C_{2+} -alcohols), together with methanol and dimethyl ether (DME), have been considered as the most important species among coal-based clean synthetic fuels and chemical feedstocks. The higher alcohols have been confirmed to be a better and cleaner automobile fuel. They feature high octane numbers, and lower emissions of NO_x , ozone, CO, and aromatic vapors. Recently, use of methyl *tert*-butyl ether (MTBE) has been prohibited in some countries or regions as additive of oil-based fuel due to the new regulations in environment protection. This change has greatly renewed interest in conversion of syngas via hydrogenation to C_{2+} -oxygenates as gasoline blends.

Higher alcohol synthesis (HAS) on the catalysts containing Mo, Group VIII metals and alkali have been extensively studied since the 1980s. Progress in this field has contributed considerably to the growing understanding of the nature of those catalytic reaction systems. Nevertheless, the existing technology of HAS is still on a small scale. The single-pass-conversion of the feed syngas and selectivity to C_{2+} -alcohols are both relatively low. Most systems produce methanol (over alkali-promoted MoS_2 catalysts) or hydrocarbons (over modified Fischer-Tropsch catalysts) as the main product instead of C_{2+} -alcohols. Development of catalysts with high efficiency and selectivity for HAS has been one of the key objectives for R&D efforts.

Multiwalled carbon-nanotubes (symbolized as “MWCNTs” and simplified as “CNTs”), as a type of novel nano-carbon support or promoter of catalyst, have been drawing increasing attention since their discovery. This kind of nanotube-C possesses several unique features, such as highly graphitized tube-wall, nanosized channel and sp^2 -C-constructed surface. They also display exceptionally high mechanical strength, high thermal/electrical conductivity, medium to high specific surface areas, and excellent performance for adsorption and spillover of hydrogen, which render this kind of nanostructured carbon materials full of promise as a novel support or promoter of catalyst. The catalytic studies conducted so far on CNT-based systems have shown encouraging results in terms of activity and selectivity.

In the present work, a series of Ni-Mo-K oxide-based catalysts supported or promoted by the simple CNTs or metallic Ni-decorated CNTs were developed. The performance of the catalyst for HAS from syngas was evaluated, and compared with the related reference

systems. The catalysts were characterized by means of SEM/TEM/EDS, XRD, XPS, LRS and H₂-TPD, and the nature of promoter action by the CNT-based nano-materials was discussed. The results shed some light on understanding the mechanism of promoter action by the CNT-additive and on the design of practical catalysts for the HAS. The progress obtained in the present work was briefly described as follows.

1. Development of CNTs-supported Ni-Mo-K catalysts for HAS from syngas

1.1 Performance of CNTs-supported Ni-Mo-K oxide-based catalyst for HAS from syngas

With a kind of home-made “Herringbone-type” multi-walled carbon nanotubes (noted as “CNTs”) as support, a type of novel CNT-supported Ni-Mo-K catalysts for HAS from syngas were prepared by a stepwise incipient wetness method, and their catalytic activity for HAS from syngas was evaluated and compared with that of the counterpart supported on activated carbon (AC) and non-supported co-precipitated Ni-Mo-K reference system. The results showed that over the 15%Ni₁Mo₁K_{0.05}/CNTs catalyst under the reaction conditions of 5.0 MPa, 538 K, H₂/CO/N₂ = 45/45/10 (v/v) and GHSV = 5000 mL_{STP}•h⁻¹•g_{cat}⁻¹ (outlet), the observed C-based selectivity of the oxygenate products (C₁₋₃-alc.+DME) reached 59.0% at the CO hydrogenation-conversion of 11.9%, with the corresponding space-time-yield (STY) of total oxygenate products reaching 205 mg•h⁻¹•g⁻¹. This value was 1.16 times that (176 mg•h⁻¹•g_{cat}⁻¹) of the 35%Ni₁Mo₁K_{0.05}/AC catalyst with the optimal Ni₁Mo₁K_{0.05} loading, and 1.76 times that (116 mg•h⁻¹•g_{cat}⁻¹) of the CNT-free non-supported co-precipitated Ni₁Mo₁K_{0.05} host system, under the same reaction conditions.

1.2 Characterizations of CNTs-supported Ni-Mo-K oxide-based catalyst

The results of the catalyst characterizations by XRD and XPS revealed that the CNT-support has strong influence on the chemical states of catalyst via its interaction with the supported Ni-Mo components, leading to the increase of the molar percentage of NiO(OH) and Mo⁴⁺/Mo⁵⁺ (the two kinds of catalytically active surface-species associated closely to selective formation of C₁₋₃-alcohols) and the dramatic decrease of the molar percentage of Ni⁰ and Mo⁰ (the two kinds of catalytically active surface-species associated closely to selective formation of hydrocarbons, especially methanation of CO). On the other hand, the

CNT-support also provided the sp^2 -C surface-sites for adsorption-activation of H_2 , which would generate surface micro-environments with high stationary-state concentration of H-adspecies in the form of sp^2 -C-H on the functioning catalyst. Those active H-adspecies could be readily transferred to $Ni_lMo_jK_k$ active sites via CNT-promoted hydrogen-spillover and thus increase the rate of surface hydrogenation reactions in the HAS. The aforementioned factors all contribute to an increase in selectivity of generating $C_{1\sim3}$ -alcohols.

2. Development of metallic Ni-decorated CNTs-promoted co-precipitated Ni-Mo-K oxide-based catalyst for HAS from syngas

2.1 Preparation and characterization of metallic Ni-decorated CNTs

With the home-made “Herringbone-type” CNTs as substrate, a type of metallic Ni-decorated CNTs (symbolized as $y\%Ni/CNTs$, where $y\%$ represents mass percentage) was prepared via a microwave irradiation-assisted polyol-reduction/deposition method, with 4.8% of Ni-loading amount being the optimal, as evidenced by the optimization tests. The results of characterization by TEM/SEM/EDX and XRD showed that, in the prepared 4.8%Ni/CNTs, the metallic Ni nanoparticles were fairly uniform in shape and size and well dispersed on the surface of CNTs, with the Ni-particle diameters being below 6 nm, and C, O and Ni were the only three elements at the surface of 4.8%Ni/CNTs, with atomic percentage of 94.4%, 4.5% and 1.1%, respectively. The H_2 -TPD test revealed that the modification of an appropriate amount of metallic Ni to the CNTs led to a significant increase in their hydrogen-adsorbing capacity, with the 4.8%Ni/CNTs reaching a maximum increment of 2.1 times (with the ratio of relative area-intensity of the observed H_2 -TPD profiles estimated to be $S_{4.8\%Ni/CNTs}/S_{CNTs} = 100/32$) in the temperature range of 273~873 K.

2.2 Performance of metallic Ni-decorated CNT-promoted co-precipitated Ni-Mo-K oxide-based catalyst for HAS from syngas

Using the $y\%Ni/CNTs$ as promoter, a type of co-precipitated Ni-Mo-K oxide-based catalysts, noted as $Ni_lMo_jK_k-x\%(y\%Ni/CNTs)$, was developed, with excellent performance for the selective formation of $C_{1\sim3}$ -alcohols from syngas. Over the composition-optimized

catalyst of $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}\text{-10.8\%}(4.8\%\text{Ni/CNTs})$ under reaction condition of 5.0 MPa, 558 K, $\text{H}_2/\text{CO}/\text{N}_2 = 45/45/10$ (v/v) and $\text{GHSV} = 5000 \text{ mL}_{\text{STP}}\cdot\text{h}^{-1}\cdot\text{g}_{\text{-cat}}^{-1}$ (outlet), the observed conversion of CO hydrogenation reached 18.0%, with the corresponding STY of total oxygenate products ($\text{C}_{1-3}\text{-alc.}+\text{DME}$) being $379 \text{ mg}\cdot\text{h}^{-1}\cdot\text{g}_{\text{-cat}}^{-1}$. This value of $\text{STY}_{\text{Total-oxy.}}$ was 1.2 and 1.7 times that ($317 \text{ mg}\cdot\text{h}^{-1}\cdot\text{g}_{\text{-cat}}^{-1}$) of the simple CNT-doped counterpart ($\text{Ni}_1\text{Mo}_1\text{K}_{0.05}\text{-10.8\%CNTs}$) and that ($218 \text{ mg}\cdot\text{h}^{-1}\cdot\text{g}_{\text{-cat}}^{-1}$) of CNT-free host system, $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$, respectively, under the same reaction condition.

2.3 Characterization of metallic Ni-decorated CNT-promoted co-precipitated Ni-Mo-K oxide-based catalyst

The addition of a minor amount of the Ni-decorated CNTs into the $\text{Ni}_i\text{Mo}_j\text{K}_k$ host catalyst caused little change in the apparent activation energy for the HAS, but led to the increase of the molar percentage of $\text{NiO}(\text{OH})$ and $\text{Mo}^{4+}/\text{Mo}^{5+}$ (the two kinds of catalytically active surface-species associated closely to selective formation of $\text{C}_{1-3}\text{-alcohols}$) and the dramatic decrease of the molar percentage of Ni^0 and Mo^0 (the two kinds of catalytically active surface-species associated closely to selective formation of hydrocarbons, especially methanation of CO), as evidenced by our XPS and XRD investigations of the tested catalysts.

The laser Raman spectroscopic (LRS) studies revealed that the difference of the CNT-containing co-precipitated catalysts, $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}\text{-10.8\%}(4.8\%\text{Ni/CNTs})$ and $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}\text{-10.8\%CNTs}$, from the CNT-free $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$ host system lies not simply in their capability of adsorbing hydrogen, but also in the property of H-adspecies on the two types of systems. The H-adspecies detected on the H_2 -prereduced catalysts of $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}\text{-10.8\%}(4.8\%\text{Ni/CNTs})$ and $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}\text{-10.8\%CNTs}$ were the H(a) adsorbed on $sp^2\text{-C}$ -sites (with the $\nu_{\text{C-H}}$ at 2935 and 3233 cm^{-1} for $-\text{CH}_2$ and $-\text{CH}$, respectively), while those detected on the H_2 -prereduced $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$ host were the H(a) adsorbed on Ni^0 -sites and Mo^0 -sites (with the $\nu_{\text{Ni-H}}$ and $\nu_{\text{Mo-H}}$ at 1983 and 1878 cm^{-1} , respectively). On the CNT-free $\text{Ni}_1\text{Mo}_1\text{K}_{0.05}$ host system, high hydrogenation activity of H-species adsorbed zero-valence metal (Ni^0 and Mo^0) sites enhanced the tendency of CO hydrogenation to generate hydrocarbon, thus leading to considerable increase of $S_{\text{Total-HC}}$, together with marked decrease of $S_{\text{Total-oxy.}}$.

It could be inferred from the H_2 -TPD measurements that the excellent adsorption performance of the CNTs, especially Ni-decorated CNTs, for H_2 would be conducive to

generating a surface micro-environment with a high stationary-state concentration of H-adspecies in the form of sp^2 -C-H on the functioning catalyst. Those active H-adspecies could be readily transferred to the $Ni_iMo_jK_k$ sites active catalytically via the CNT-promoted hydrogen-spillover, thus increase the rate of a series of surface hydrogenation reactions. In addition, high concentration of H-adspecies on the catalyst would also greatly inhibit the water-gas-shift side-reaction. All these factors mentioned above contribute to an increase in the yield of C_{1-3} -alcohols.

Compared to that of the “Herringbone-type” CNTs, the surface of the “Parallel-type” CNTs possesses less dangling bonds, thus lower chemical activity. It is probably this peculiarity that renders the “Parallel-type” CNTs to have lower capability for adsorption and activation of H_2 , as evidenced by H_2 -TPD measurements, thus showing the rather limited promoter effect.

In sharp contrast to the CNTs(or 4.8%Ni/CNTs)-doped systems, the addition of activated carbon (AC, a kind of amorphous carbon with 830 m^2/g of N_2 -BET-SSA) into the $Ni_1Mo_1K_{0.05}$ host catalyst not only did not help improve the performance of the catalyst, but also led to a certain decrease in conversion of the CO hydrogenation and STY of the total oxygenate products (C_{1-3} -alc.+DME).

3. Conclusion

- 1) It is evident that the CNTs or CNT-based materials decorated by metallic Ni could act as a novel carrier and/or promoter of the Ni-Mo-K oxide-based catalyst for HAS from syngas. The (4.8%Ni/CNTs)-doped co-precipitated $Ni_1Mo_1K_{0.05}$ catalyst achieves highly effective and selective formation of C_{1-3} -alcohols from syngas.
- 2) The promoter action by the CNTs was mainly in providing the sp^2 -C surface-sites for adsorption-activation of H_2 (one of the reactants), while simultaneously enhancing the molar percentage of the two kinds of surface species active catalytically, NiO(OH) and Mo^{4+}/Mo^{5+} (both associated closely to selective formation of C_{1-3} -alc.), via affecting the chemical states of catalyst.
- 3) Appropriate decoration of the CNTs by a minor amount of metallic Ni could improve the capability of CNT's adsorbing H_2 , rendering their promoter action more remarkable.

The results of the present work also shed some light on the understanding of the promoter

action by the transition metal-decorated CNTs-additive and on the design of practical catalyst for HAS from syngas. For better understanding of nature of the promoting action by CNT-based nano-materials, especially the mechanism of improving selective formation of the higher (C_{2+}) alcohols, further studies, especially *in-situ* characterization of reaction intermediates under the HAS reaction condition, are highly needed.

Keywords: Multi-walled carbon nanotubes; metallic Ni-decorated MWCNTs; Ni-Mo-K catalyst; CO hydrogenation; higher alcohol synthesis

目录

第一章 绪论	1
1.1 混合醇合成	1
1.1.1 低碳醇合成的工业背景	1
1.1.2 合成低碳醇的工艺技术	2
1.1.3 低碳醇合成的主要催化剂体系及其特点	9
1.1.4 低碳醇合成反应热力学 ^[16,29,58]	10
1.1.5 低碳醇合成机理	11
1.2 碳纳米管	16
1.2.1 碳纳米管的结构	16
1.2.2 碳纳米管的制备方法	17
1.2.3 碳纳米管的纯化	19
1.2.4 碳纳米管的应用	22
参考文献	25
第二章 实验部分	34
2.1 主要试剂及原料	34
2.2 催化剂制备	34
2.2.1 碳纳米管的制备	34
2.2.2 镍修饰碳纳米管材料的制备	34
2.2.3 负载型催化剂的制备	35
2.2.4 共沉淀催化剂的制备	35
2.3 催化剂的活性评价	35
2.4 产物分析计算方法	36
2.5 催化剂物化性能表征	37
2.5.1 程序升温 H ₂ 还原 (H ₂ -TPR)	37
2.5.2 H ₂ 程序升温脱附 (H ₂ -TPD)	38
2.5.3 TEM、SAED、SEM、EDX、XRD、XPS 及比表面观测	38
2.5.4 原位共焦显微拉曼光谱表征 (LRS)	39
参考文献	39

第三章 碳纳米管负载合成气(CO/H ₂)制低碳混合醇 Ni-Mo-K 氧化物基催化剂的研究.....	40
3.1 前言	40
3.2 负载型催化剂不同载体上最佳负载量的优化	41
3.2.1 x%Ni ₁ Mo ₁ K _{0.05} /CNTs 催化剂上 Ni-Mo-K 负载量的优化.....	42
3.2.2 x%Ni ₁ Mo ₁ K _{0.05} /AC 催化剂上 Ni-Mo-K 负载量的优化.....	42
3.3 5.0 MPa 压力级别反应条件下催化剂的活性评价	44
3.3.1 反应温度对低碳醇合成反应性的影响	44
3.3.2 空速对低碳醇合成反应性的影响	45
3.3.3 不同载体最佳负载量和非负载体系的活性对比研究	47
3.4 催化剂的物化性能表征	52
3.4.1 加氢活化能	52
3.4.2 XRD 表征.....	53
3.4.3 XPS 表征.....	54
3.4.4 H ₂ -TPD 表征	58
3.5 本章小结	59
参考文献.....	60
第四章 过渡金属镍修饰碳纳米管的制备和表征.....	62
4.1 前言	62
4.2 镍修饰碳纳米管材料的制备	67
4.2.1 碳纳米管的制备	67
4.2.2 碳纳米管的纯化及表面酸含量的测定	67
4.2.3 Ni/CNTs 材料的制备.....	68
4.3 镍修饰碳纳米管材料制备参数的优化及物化性能的表征	68
4.3.1 Ni/CNTs-1 上 Ni 最佳负载量的优化及物化性能表征	68
4.3.2 不同还原温度对 4.5%Ni/CNTs-1 吸脱附氢的影响	73
4.3.3 CNTs 的不同纯化方法对 Ni/CNTs 材料的影响	75
4.3.4 Ni/CNTs-3 上 Ni 最佳负载量的优化及物化性能表征	78
4.3.5 CNTs 与镍之间相互作用研究.....	86
4.4 讨论	88
4.5 本章小结	89

Degree papers are in the “[Xiamen University Electronic Theses and Dissertations Database](#)”. Full texts are available in the following ways:

1. If your library is a CALIS member libraries, please log on <http://etd.calis.edu.cn/> and submit requests online, or consult the interlibrary loan department in your library.
2. For users of non-CALIS member libraries, please mail to etd@xmu.edu.cn for delivery details.

厦门大学博硕士论文摘要库